

## Compact Undercounter Refrigerator Models/Self-Contained



**Model KUHT27-R**  
(shown with optional casters)



Stainless Exterior

### 27", 32", 48", 60 & 72" Wide Models

27" One Door Refrigerator Hinged Left	KUHT27-L
27" One Door Refrigerator Hinged Right	KUHT27-R
32" One Door Refrigerator Hinged Left	KUHT32-L
32" One Door Refrigerator Hinged Right	KUHT32-R
48" Two Door Refrigerator Hinged Left/Right	KUHT48-LR
60" Two Door Refrigerator Hinged Left/Right	KUHT60-LR
72" Two Door Refrigerator Hinged Left/Right	KUHT72-LR

Kairak's durable, high performance, compact undercounter refrigerator models provide a high quality/high value alternative to the all too common commodity types in today's market.

Durable, built with stainless steel exteriors and anodized aluminum interiors, their heavy duty cabinet construction promises years of useful service. Truly front breathing, their design allows for "zero-clearance" installation. As a result they can be placed right up against the back wall and alongside other kitchen equipment, saving valuable floor space.

Additionally, they offer a wide range of optional accessories to choose from, and are ideal for use with many different type applications.

## Standard Product Features

- Stainless Steel Exterior Top, Sides & Doors
- Anodized Aluminum Interior
- Front Breathing Self-Contained Refrigeration System
- Environmentally Friendly R-134a Refrigerant
- Self-Closing Stainless Steel Doors With Stay Open Feature At 105 Degrees
- Anodized Aluminum Interior Door Liner
- Interior Mounted Thermometer
- Two (2) Powder Coated Shelves Per Door, Mounted On Pilasters
- Automatic Non-Electric Condensate Evaporator
- Magnetic Snap-In Door Gaskets
- 8' Cord & Plug Attached
- Set of Four (4) 6" High Adjustable Legs (6 For 60" & 72" models)
- Three Year Parts And Labor Warranty
- Five Year Compressor Warranty

## Optional Accessory Kits\*

- **CASTER 5SET4** (four 6" high casters for 27", 32" & 48" models)
- **CASTER 5SET6** (six 6" high casters for 60" & 72" models)
- **CASTER SET4IN** (four 4" high casters for 27", 32" & 48" models)
- **CASTER 60SET3** (six 4" high casters for 60" & 72" models)
- **CASTER SET3IN** (four 3-1/2" high casters for 27", 32" & 48" models)
- **CASTER SET4** (six 3-1/2" high casters for 60" & 72" models)
- **CASTER SET2IN** (four 2-1/2" high casters for 27" models)
- **SHELF CPW1** (additional shelf for all 27" models)
- **SHELF CPW2** (additional shelf for all 32" models)
- **SHELF48 UPPER** (upper shelf for all 48" models)
- **SHELF48 LOWER** (lower shelf for all 48" models)
- **SHELF60 UPPER** (upper shelf for all 60" models)
- **SHELF60 LOWER** (lower shelf for all 60" models)
- **SHELF72 UPPER** (upper shelf for all 72" models)
- **SHELF72 LOWER** (lower shelf for all 72" models)

\*Optional accessory kits shipped separately for field installation.

## Factory Installed Options

- Stainless Steel Finished Back
- **CU27TOP BSWO** (22 ga. stainless steel top with 4" backsplash for models KUHT27)
- **CU32TOP BSWO** (22 ga. stainless steel top with 4" backsplash for models KUHT32)
- **CU48TOP BSWO** (22 ga. stainless steel top with 4" backsplash for models KUHT48)
- **CU60TOP BSWO** (22 ga. stainless steel top with 4" backsplash for models KUHT60)
- **CU72TOP BSWO** (22 ga. stainless steel top with 4" backsplash for models KUHT72)
- Other Door Hingings



Listed by Underwriters Laboratories Inc., to U.S. and Canadian safety standards and NSF International in accordance with ANSI/NSF7.

Approval: \_\_\_\_\_

# Specifications

## Construction, Hardware and Insulation

Cabinet exterior front, one piece sides, and doors are constructed of 22 gauge stainless steel. Cabinet interior and door liners are constructed of anodized aluminum. The exterior cabinet back and bottom are constructed of galvanized steel.

Door self close at less than 90 degrees and also include a stay open feature at 105 degrees. Easily removable for cleaning, vinyl magnetic door gasket assures tight door seal. Both the cabinet and door(s) are insulated with an average of 2" thick high density, non-CFC, foamed in place polyurethane.

## Refrigeration System

A balanced, rear mounted, front breathing, self-contained refrigeration system using R-134a refrigerant is provided. It features a capillary tube metering device, air-cooled hermetic compressor, a forced air evaporator coil and a non-electric condensate evaporator. An 8' cord and plug is provided. Standard operating temperature for refrigerator models is 34 to 38°F.

## Interior

Standard interior arrangements include two (2) powder coated wire shelves per door, mounted on pilasters. These are adjustable in 1/2" increments, allowing for a minimum of 1-1/2" spacing between shelves.

## Warranties

Both a three year parts and labor warranty and a five year compressor warranty (self-contained models only) are provided standard.

Cabinet Dimensional Data								
Model	Storage cu. ft.	A Width - cabinet	B Width - door	C Depth - door open 90°	Clear door opening	# of doors	# of shelves	Total shelf area sq. ft.
KUHT27	7.1	27"	25 7/8"	55 3/8"	22 3/4"	1	2	4.88
KUHT32	8.8	32"	30 13/16"	60 3/8"	27 3/4"	1	2	6.1
KUHT48	13.1	48"	21 1/8"	50 5/8"	18"	2	4	10.3
KUHT60	16.7	60"	25 7/8"	55 3/8"	22 3/4"	2	4	13.2
KUHT72	20	72"	30 13/16"	60 3/8"	27 3/4"	2	4	15.5

Electrical & Refrigeration Data			Shipping Data		
115/60/1 R-134a NEMA 5-15P			(42"D x 41"H)		
Model	Full Load Amps	BTU/HR - HP	Width - crated	Volume - crated cu. ft.	Weight - lbs.
KUHT27	4.7	889 (1/6)	45"	45	240 net/275 gross
KUHT32	5.8	889 (1/6)	45"	45	255 net/300 gross
KUHT48	5.5	1869 (1/4)	69"	69	355 net/400 gross
KUHT60	5.5	1869 (1/4)	69"	69	457 net/500 gross
KUHT72	6.3	1650 (1/4)	84"	84	548 net/575 gross

## NOTES:

- 1= Based on a 90 degree F ambient and 20 degree F evaporator.
- 2= When ordering please specify: voltage, hinging, optional accessories and any additional warranties.
- 3= Continued product development may necessitate specification changes without notice.

